

Tectyl Clean 640

High solvency power solvent type cleaner



| INTRODUCTION |

Tectyl Clean 640 is an intensive wax, grease, gum cleaning products. Tectyl Clean 640 is a petroleum Solvent with low CA content. Tectyl Clean 640 efficiently and economically removes these soils ; grease, cutting chips, light drawing compound, heavy rust preventive coatings and typical shop dirt.

| PHYSICAL PROPERTIES |

Appearance	Clear liquid	Naked Eye
Specific Gravity (15/4°C)	0.77	KS M 2002
Flash Point (°C)	40	KS M 2010
Aniline Point (°C)	70	KS M 2053
Distillation Range	Initial	159
	50%	172
	Final	193
		KS M 2031

- All data given in this Product Data Sheet are typical of this Product. It does not however constitute a specification. And, We reserve the right to modify products without prior notice.

| HOW TO USE |

Dipping, Spray, Ultra-Sonic, Hand Wiping etc.

| FEATURES |

Tenacious soils such as heavy duty cutting oils, drawing compounds and grease, wax type coating may require only Tectyl Clean 640 no added water.

| APPLICATION |

All contaminated part ; Automotive parts, precision bearings, machined part, crankshaft, bar and drill stock etc.

| CAUTION |

Avoid flammable.

| PACKING & SAFETY |

- Tank/Lorry, Tote, Drum(200LT), Pail(20LT)
- For your Safety, Refer to the Material Safety Data Sheet.