-tul

Tertu

# **Tectyl Form 325A**

Metal Cold forming Fluids

#### | INTRODUCTION | -----

Tectyl Form 325A is a newly developed high speed nut tapping oil. Its highly refined base oil provides mild odor and good appearance as well as extremely less fuming which enables excellent atmosphere of shop area. The extreme pressure additive package and refined oil incorporated into Tectyl Form 325A causes no stain and rust to the forming parts.

## | FEATURES | -----

- Quite less fuming and applicable even in winter season
- Excellent oxidative stability and long sump life
- Improved surface finish and no scratching
- Excellent machining capability
- Excellent lubricity and extreme EP
- Improved forming performance

## APPLICATION |-----

Tectyl Form 325A is a cold forging oil designed especially for use in high speed nut tapping

• Material : General Steel, Alloy Steel, Stainless Steel

### | PHYSICAL PROPERTIES | -----

Appearance	Transparent yellow
Specific gravity (15/4°C)	0.89
Viscosity (40°C, cSt)	24
Liquidity point (°C)	- 15

- All data given in this Product Data Sheet are typical of this Product. It does not however constitute a specification. And, We reserve the right to modify products without prior notice.

#### | PACKAGING & SAFETY | ------

- Tank/Lorry, Tote, Drum(200LT), Pail(20LT)
- For your Safety, Refer to the Material Safety Data Sheet,



