



# SERIOLA D TH

Cleaning additive for heat transfer circuits.

## APPLICATIONS

Heat transfer oils circuits  
cleaning before drain

- **SERIOLA D TH** is used diluted in the fluid of the circuit requiring cleaning.
- **SERIOLA D TH** is only used for cleaning operations
- Add 5 % minimum of **SERIOLA D TH** in the circuit 24 to 48 hours before oil change while maintaining the fluid circulation at the normal use temperature (250 °C or more).
- Replace the filters before refilling the circuit with new oil.

## ADVANTAGES

high heat transfer efficiency

Running safety

- **SERIOLA D TH** has a high detergency and dispersiveness level; an excellent thermal stability.
- **SERIOLA D TH** is completely miscible with all mineral-based heat transfer oils. Please contact technical support for details of use with synthetic heat transfer oils.

CARACTERISTIQUES TYPES	METHODS	UNITS	SERIOLA D TH
Specific gravity at 15 °C	ISO 3675	kg/m <sup>3</sup>	910
Kinematic viscosity at 40 °C	ISO 3104	mm <sup>2</sup> /s	24.5
Kinematic viscosity at 100 °C	ISO 3104	mm <sup>2</sup> /s	4.8
Flash point OC	ISO 2592	°C	203
Aniline point	ASTM D 611	°C	58

Les valeurs des caractéristiques figurant dans ce tableau sont des valeurs typiques données à titre indicatif.

INDUSTRIE AVIATION SPECIALITES

11 may 2001  
SERIOLA D TH



1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser.