# SAFETY DATA SHEET Castrol

Alphasyn GS 680

Section 1. Identification			
Product name	Alphasyn GS 680		
SDS no.	467095		
Code	467095-DE08		
Relevant identified uses of	of the substance or mixture and uses advised against		
Product use	Gear lubricant For specific application advice see appropriate Technical Data Sheet or consult our company representative.		
Supplier	Castrol BP Petco 9th Floor – Times Square building 57-69F Dong Khoi Street District 1, Ho Chi Minh City Vietnam Tel: 84-8-38219596 / 38219153 Fax: 84-8-38219603 / 38219152		
EMERGENCY SPILL INFORMATION:	Carechem: +65 3158 1074 (24/7)		

### Section 2. Composition, information on ingredients

Substance/mixture Mixture

Polyalkylene glycol. Proprietary performance additives.

Ingredient name	CAS number	%
Benzenamine, N-phenyl-, reaction products with 2,4, 4-trimethylpentene	68411-46-1	≤3
N-alkylated benzotriazoles, (Isomers - mixture)	94270-86-7 (80584-90-3 / 80595-74-0)	≤0.3

**Format Vietnam** 

(Vietnam)

Page: 1/10

(ENGLISH)

Language ENGLISH

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 3. Hazards identification

 Classification of the substance or mixture
 SKIN SENSITISATION - Category 1

 GHS label elements
 Hazard pictograms

 Variation
 Variation of the substance or mixture

 Signal word
 Warning

 Product name Alphasyn GS 680
 Product code
 467095-DE08

Date of issue 11/23/2018.

Version 2

# Section 3. Hazards identification

Hazard statements	H317 - May cause an allergic skin reaction.
Precautionary statements	
Prevention	P280 - Wear protective gloves. P261 - Avoid breathing vapour. P272 - Contaminated work clothing should not be allowed out of the workplace.
Response	P302 + P352 + P363 - IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. P333 + P313 - If skin irritation or rash occurs: Get medical attention.
Storage	Not applicable.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Routes of entry	Dermal contact. Eye contact. Inhalation.
Other hazards which do not result in classification	Defatting to the skin.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. In the event of any complaints or symptoms, avoid further exposure. Get medical attention.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.

#### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Product name Alphasyn GS 680			Product code	467095-DE08	Page: 2/10
Date of issue	11/23/2018.	Format	Vietnam	Language	ENGLISH
Version 2			(Vietnam)		(ENGLISH)

### Section 5. Firefighting measures

•	
Extinguishing media	
Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	Swarf fires - Neat metal working oils may fume, thermally decompose or ignite if they come into contact with red hot swarf. To minimise the generation of red hot swarf ensure that a sufficient flow of oil is correctly directed to the cutting edge of the tool to flood it throughout cutting operations. As an additional precaution swarf should be regularly cleared from the immediate area to prevent the risk of fire. In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	Combustion products may include the following: carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO <sub>2</sub> etc.)
Special protective actions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

### Section 6. Accidental release measures

Personal precautions, protecti	ve equipment and emergency procedures
For non-emergency personnel	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.
For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and material for conta	ainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Product name Alphasyn GS 680		Product code	467095-DE08	Page: 3/10		
	Date of issue	11/23/2018.	Format	Vietnam	Language	ENGLISH
	Version 2			(Vietnam)		(ENGLISH)

# Section 7. Handling and storage

Precautions for safe handling			
Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Concentrations of mist, fumes and vapours in enclosed spaces may result in the formation of explosive atmospheres. Excessive splashing, agitation or heating must be avoided. During metal working, solid particles from workpieces or tools will contaminate the fluid and may cause abrasions of the skin. Where such abrasions result in a penetration of the skin, first aid treatment should be applied as soon as reasonably possible. The presence of certain metals in the workpiece or tool, such as chromium, cobalt and nickel, can contaminate the metalworking fluid, as can bacteria, and as a result may induce allergic and other skin reactions, especially if personal hygiene is inadequate.		
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.		
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.		

# Section 8. Exposure controls/personal protection

#### Control parameters

#### Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Product name Alphasyn GS 680		Pr	roduct code	467095-DE08	Page: 4/10
	Date of issue 11/23/2018.	Format Vi	ietnam	Language	ENGLISH
Version 2		(V	/ietnam)		(ENGLISH)

# Section 8. Exposure controls/personal protection

Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety glasses with side shields.
Skin protection	
Hand protection	Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Skin protection	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half- mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m3), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m3). Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Product name Alphasyn GS 6	80		Product code	467095-DE08	Page: 5/10
Date of issue 1	1/23/2018.	Format	Vietnam	Language	ENGLISH
Version 2			(Vietnam)		(ENGLISH)

### Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	Liquid.
Colour	Amber.
Odour	Oily.
Odour threshold	Not available.
рН	Not available.
Melting point	Not available.
Boiling point	Not available.
Flash point	Open cup: 258°C (496.4°F) [Cleveland.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower and upper explosive (flammable) limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Density	>1000 kg/m³ (>1 g/cm³) at 15°C
Relative density	Not available.
Solubility	Miscible in water.
Partition coefficient: n- octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 680 mm²/s (680 cSt) at 40°C

# Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

Aspiration hazard

Not available.

### Information on likely routes Routes of entry anticipated: Dermal, Inhalation.

#### of exposure Potential acute health effects

6/10
ISH
_ISH)

# Section 11. Toxicological information

Eye contact	No known significant effects or critical hazards.	
Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.	
Skin contact	Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.	
Ingestion	No known significant effects or critical hazards.	
Symptoms related to the physical	sical, chemical and toxicological characteristics	
Eye contact	No specific data.	
Inhalation	No specific data.	
Skin contact	Adverse symptoms may include the following: irritation redness dryness cracking	
Ingestion	No specific data.	
Delayed and immediate effect	ts as well as chronic effects from short and long-term exposure	
<u>Short term exposure</u>		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
<u>Long term exposure</u>		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health effe	<u>cts</u>	
General	No known significant effects or critical hazards.	
Carcinogenicity	No known significant effects or critical hazards.	
Mutagenicity	No known significant effects or critical hazards.	
Teratogenicity	No known significant effects or critical hazards.	
Developmental effects	No known significant effects or critical hazards.	
Fertility effects	No known significant effects or critical hazards.	
Numerical measures of toxici	ty	
Acute toxicity estimates		

Not available.

# Section 12. Ecological information

**Toxicity** 

**Environmental effects** 

No known significant effects or critical hazards.

#### Persistence and degradability

Not expected to be rapidly degradable.

#### **Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

Product nan	ne Alphasyn GS 680		Product code	467095-DE08	Page: 7/10
	Date of issue 11/23/2018.	Format	Vietnam	Language	ENGLISH
Version 2			(Vietnam)		(ENGLISH)

# Section 12. Ecological information

<u>Mobility in soil</u>	
Soil/water partition coefficient (Koc)	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.
Other adverse effects	No known significant effects or critical hazards.
Other ecological information	Miscible in water.

### Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user

Not available.

Transport in bulk accordingNot available.to Annex II of Marpol andthe IBC Code

Product nam	1e Alphasyn GS 680		Product code	467095-DE08	Page: 8/10
	Date of issue 11/23/2018.	Format	Vietnam	Language	ENGLISH
Version 2			(Vietnam)		(ENGLISH)

### Section 15. Regulatory information

•	-
Safety, health and environmental regulations specific for the product	No known specific national and/or regional regulations applicable to this product (including its ingredients).
Toxic classification (TCVN 3164-79)	Not classified as hazardous.
International lists	
Australia inventory (AICS)	At least one component is not listed.
Canada inventory	At least one component is not listed.
China inventory (IECSC)	All components are listed or exempted.
REACH Status	The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.
Japan inventory (ENCS)	All components are listed or exempted.
Korea inventory (KECI)	At least one component is not listed.
Philippines inventory (PICCS)	At least one component is not listed.
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.
United States inventory (TSCA 8b)	At least one component is not listed.

### Section 16. Other information

**History** 

Date of issue/ Date of revision	23 November 2018
Date of previous issue	15 June 2018
Prepared by	Product Stewardship
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate</li> <li>BCF = Bioconcentration Factor</li> <li>GHS = Globally Harmonized System of Classification and Labelling of Chemicals</li> <li>IATA = International Air Transport Association</li> <li>IBC = Internediate Bulk Container</li> <li>IMDG = International Maritime Dangerous Goods</li> <li>LogPow = logarithm of the octanol/water partition coefficient</li> <li>MARPOL = International Convention for the Prevention of Pollution From Ships,</li> <li>1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)</li> <li>UN = United Nations</li> <li>Varies = may contain one or more of the following 101316-69-2, 101316-70-5,</li> <li>101316-71-6, 101316-72-7, 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4,</li> <li>64741-97-5, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6,</li> <li>64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7,</li> <li>64742-63-8, 64742-64-9, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,</li> <li>72623-87-1, 74869-22-0, 90669-74-2</li> </ul>

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

		Product code	467095-DE08	Page: 9/10		
	Date of issue	11/23/2018.	Format	Vietnam	Language	ENGLISH
	Version 2			(Vietnam)		(ENGLISH)

# Section 16. Other information

The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Alphasyn GS 680	Product code	467095-DE08	Page: 10/10
Date of issue 11/23/2018.	Format Vietnam	Langua	ge ENGLISH
Version 2	(Vietnam)		(ENGLISH)