



Alpha™ SMR Heavy X

Open Gear Lubricants

Description

Castrol Alpha™ SMR Heavy X is designed for use on heavily loaded open gears and brass journal bearings such as found in the sugar processing, mining, quarrying and rubber industries. Can also be used as a wire rope lubricant.

Application

The combination of additives includes extreme pressure additives to satisfy the vigorous lubrication demands of heavily loaded mill roll bearings and open gears. Also to protect wire ropes during the extremes of service conditions, in such applications as the protection of hoist ropes where internal wear and lubricity are of prime concern, to the severe service conditions of drag ropes where protection from abrasive dirt is the major need.

Recommended for use in the following applications:

- sugar mill roll bearing;
- heavily loaded open gears; and
- lubrication and protection of wire ropes.

Advantages

- The products impart high load carrying capabilities thereby reducing wear on contact surfaces.
- The products contain emulsifiers to resist the harmful effects of contamination with sugar juices.
- Protection for wear and corrosion.
- Resists throw-off through excellent adhesive properties.

Typical Characteristics

Name	Method	Units	SMR Heavy X
Appearance	Visual	-	Black viscous oil
Density @ 15°C	ASTM D1298	kg/m ³	997
Kinematic Viscosity @ 40°C	ASTM D445	mm ² /s	11,000
Kinematic Viscosity @ 100°C	ASTM D445	mm ² /s	200
Pour Point	ASTM D97	°C	12
Flash Point, PMCC	ASTM D93	°C	250

Subject to usual manufacturing tolerances.

Alpha™ SMR Heavy X

30 May 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 717 Bourke Street, Docklands Vic 3008

Technical Advice Line: 1300 557 998 Customer Service: 1300 722 088

<http://msdspdscastrol.com>

Page: 2/2