



Magna™ CTX WT Range

Circulating oils

Description

Castrol Magna™ CTX WT Range (previously called Magna™ XX) are a series of premium quality circulating oils that represent a significant advancement in circulating oil technology. These oils are manufactured from the highest quality base oils and are formulated with an advanced technology anti-wear additive system designed to extend service life in a broad range of systems operating under high impact and high shock loading. Magna CTX WT oils are designed to provide maximum rust and oxidation resistance while allowing the oil to rapidly separate from water, providing exceptional demulsibility characteristics.

Application

Magna CTX WT oils are engineered for use in MORGOIL™ back-up roll bearing systems such as those manufactured by Morgan Construction Company, Danieli, SMS Demag and others. These high quality oils meet or exceed the Morgoil Lubricant Specification Rev. 1.1 (27 Jan 2005), Morgoil 'Super-Demulsibility' Lubricant Specification Rev. 2.4, Danieli Standard 0.000.001 Rev. 14.

Magna CTX WT oils are recommended for use in both ferrous and non-ferrous Morgoil back-up roll bearing systems. For optimum performance, appropriate viscosity oils should be selected according to the loading, speed and manufacturer recommendations. Magna CTX WT can be applied via circulating as well as air/oil lubrication systems. Magna CTX WT circulating oils are also suitable for use on other primary mill and mini-mill bearing application systems.

MORGOIL is a trademark of Morgan Construction Company.

Advantages

- Advanced technology anti-wear additive package: Passes FZG stage 12+ and provides non-corrosive anti-wear protection in high impact and high shock load applications.
- Excellent demulsibility: Rapid water separation and hydrolytic stability means increased corrosion protection and reduced down time through prolonged lubricant life and increased equipment reliability.
- Superior thermal and oxidative stability: Provides reliable performance and extends oil life in severe applications.
- Minimal deposit formation: Cleaner system and reduced filter change frequency.
- Protection against rust and corrosion: Prevents corrosive activity on bearings and metal surfaces.
- Environmentally friendly: Does not contain zinc, phenol, or heavy metals.

Typical Characteristics

Name	Method	Units	100	150	220	320	460	680
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	890	890	890	890	890	910
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	97.3	149	222	320	474	682
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	11.43	14.6	19.1	24.5	31.9	37.5
Viscosity Index	ISO 2909 / ASTM D2270	-	105	97	97	98	97	92
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	235/ 455	246/ 475	246/ 475	246/ 475	246/ 475	243/ 469
Pour Point	ISO 3016 / ASTM D97	°C/°F	-24/-11	-21/-6	-15/5	-12/10	-9/16	-6/21
Water Separation @ 82°C / 180°F (40/37/3)	ISO 6614 / ASTM D1401	min	10	10	15	15	20	20
Dynamic Demulsibility Endurance, Water in Oil	Morgan test	%	2.3	4.8	7.8	8.4	10	12
Dynamic Demulsibility Endurance, Oil in Water	Morgan test	%	Trace	Trace	Trace	Nil	Nil	Nil
Rust test - distilled water (24 hrs)	ISO 7120 / ASTM D665A	-	Pass	Pass	Pass	Pass	Pass	Pass
Rust test - synthetic seawater (24 hrs)	ISO 7120 / ASTM D665B	-	Pass	Pass	Pass	Pass	Pass	Pass
Copper corrosion (3 hrs@100°C/ 212°F)	ISO 2160 / ASTM D130	Rating	1a	1a	1a	1a	1a	1a
Foam Sequence I - tendency / stability	ISO 6247 / ASTM D892	ml/ml	0/0	0/0	0/0	0/0	0/0	0/0
Foam Sequence II - tendency / stability	ISO 6247 / ASTM D892	ml/ml	0/0	0/0	0/0	0/0	0/0	0/0
Foam Sequence III - tendency / stability	ISO 6247 / ASTM D892	ml/ml	0/0	0/0	0/0	0/0	0/0	0/0
Four Ball Wear test - Wear Scar Diameter (40 kgf / 75°C / 1200 rpm / 1 hr)	ASTM D2266	mm	0.32	0.32	0.32	0.3	0.3	0.3
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	12+	12+	12+	12+	12+	12+
Oxidation Stability Rotating Pressure Vessel test	ASTM D2272	min	1020	517	515	368	420	180

Subject to usual manufacturing tolerances.

This product was previously called Magna XX. The name was changed in 2015.

Magna™ CTX WT Range

26 Oct 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 717 Bourke Street, Docklands Vic 3008
Technical Advice Line: 1300 557 998 Customer Service: 1300 722 088

<http://msdspd.castrol.com>

Page: 3/3