SAFETY DATA SHEET



Castrol Moly Grease

Section 1. Identification

GHS product identifier Castrol Moly Grease
Product code 452715-TH01
SDS no. 452715

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Grease

mixture For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Manufacturer BP-Castrol (Thailand) Limited

Samut Sakon Industrial Estate, 39/77-78 Moo 2 Rama II Road,

Bangkachao Amphur Muang, Samut Sakorn 74000

Tel. +66 34 419666, Fax. +66 34 419666

Supplier BP-Castrol (Thailand) Limited

3 Rajanakarn Building, 23rd Floor South Sathon Road Yannawa, Sathon Bangkok 10120

Tel. +66 02 6843555, Fax. +66 02 684 3646

EMERGENCY TELEPHONE

NUMBER

Carechem: 001800 1 2066 6751 (tollfree, access from Thailand only)

Section 2. Hazards identification

GHS Classification SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A

GHS label elements
Hazard pictograms

!

Signal word Warning

Hazard statements H319 - Causes serious eye irritation.

H315 - Causes skin irritation.

Precautionary statements

Prevention P280 - Wear protective gloves. Wear eye or face protection.

P264 - Wash hands thoroughly after handling.

Response \$\overline{\mathfrak{7}}302 + P352 + P362 + P363 - IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing. Wash contaminated clothing before reuse.

P332 + P313 - If skin irritation occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

Storage Not applicable.

Disposal Not applicable.

ther hazards which do not Defatting to the skin.

Other hazards which do not result in classification No

on Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure

constitute a major medical emergency.

See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data

Sheet.

 Product name Castrol Moly Grease
 Product code
 452715-TH01
 Page: 1/8

 Version 2.01
 Date of issue 09/02/2017.
 Format GHS - Thailand
 Language ENGLISH

 Build 5.0.2
 (GHS - Thailand)
 (ENGLISH)

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Thickening agent. Proprietary performance additives.

Ingredient name	%	CAS number
Base oil - unspecified	≥90	Varies - See Key to abbreviations
Lithium hydroxide monhydrate phosphorodithioic acid, O,O - di- C1-14- alkyl esters zinc salts	≤2.9 ≤3	1310-66-3 68649-42-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Do not induce vomiting unless directed to do so by medical personnel. Never give Ingestion

anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse

health effects persist or are severe.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes Skin contact

while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention.

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eve contact

Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for

and remove any contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments No specific treatment.

Notes to physician reatment should in general be symptomatic and directed to relieving any effects.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with

extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide

product considerable distances along tissue planes.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

extinguisher or spray.

Unsuitable extinguishing

media

Do not use water jet.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products Combustion products may include the following:

carbon dioxide carbon monoxide sulphur oxides phosphorus oxides metal oxide/oxides

Product name Castrol Molv Grease Product code 452715-TH01 Date of issue 09/02/2017. Language ENGLISH Format GHS - Thailand Version 2.01

> (ENGLISH) Build 5.0.2 (GHS - Thailand)

Page: 2/8

Section 5. Firefighting measures

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Contact emergency personnel.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. If emergency personnel are unavailable, contain spilt material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid breathing vapour or mist. Avoid contact with eyes, skin and clothing. Do not ingest. Empty containers retain product residue and can be hazardous. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Product name Castrol Moly GreaseProduct code452715-TH01Page: 3/8Version 2.01Date of issue 09/02/2017.Format GHS - ThailandLanguage ENGLISHBuild 5.0.2(GHS - Thailand)(ENGLISH)

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
'	ACGIH TLV (United States). TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction	

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Eye protection Skin protection

Safety glasses with side shields.

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

rease of insufficient ventilation, wear suitable respiratory equipment. For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m3), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m3).

Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Product name Castrol Molv Grease

Version 2.01

Product code 452715-TH01 Page: 4/8

Date of issue 09/02/2017.

Format GHS - Thailand Language ENGLISH (ENGLISH)

Section 9. Physical and chemical properties

Appearance

Physical state Liquid. Colour Grey. [Dark] Odour Not available. Not available. Odour threshold pН Not available. **Melting point** Not available. **Boiling point** Not available. >180 °C **Drop Point** Flash point Not available. **Evaporation rate** Not available.

Flammability (solid, gas) Not applicable. Based on - Physical state

Lower and upper explosive

(flammable) limits

Not available.

Vapour pressure Not available. Vapour density Not available. Relative density Not available. insoluble in water. Solubility Partition coefficient: n-Not available. octanol/water

Not available. Auto-ignition temperature **Decomposition temperature** Not available. Not available. **Viscosity**

Section 10. Stability and reactivity

No specific test data available for this product. Refer to Conditions to avoid and Reactivity

Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products products

should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Information on likely routes

of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact Causes serious eye irritation.

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low

vapour pressure.

Skin contact Causes skin irritation. Defatting to the skin. Irritating to mouth, throat and stomach. Ingestion

redness

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact Adverse symptoms may include the following:

> pain or irritation watering

Inhalation No specific data.

Product name Castrol Moly Grease 452715-TH01 Product code Page: 5/8 Date of issue 09/02/2017. Language ENGLISH Version 2.01 Format GHS - Thailand

Build 5.0.2 (GHS - Thailand) (ENGLISH)

Section 11. Toxicological information

Skin contact Adverse symptoms may include the following:

irritation redness dryness cracking

Ingestion No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation Inhalation of oil mist or vapours at elevated temperatures may cause respiratory

irritation.

Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	33018.2 mg/kg

Section 12. Ecological information

Environmental effects No known significant effects or critical hazards.

Persistence and degradability

Expected to be biodegradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

MobilitySpillages are unlikely to penetrate the soil.Other adverse effectsNo known significant effects or critical hazards.Other ecological informationThis product is unlikely to disperse in water.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA	
UN number	Not regulated.	Not regulated.	
UN proper shipping name	-	-	
Transport hazard class(es)	-	-	
Packing group	-	-	

 Product name Castrol Moly Grease
 Product code
 452715-TH01
 Page: 6/8

 Version 2.01
 Date of issue 09/02/2017.
 Format GHS - Thailand
 Language ENGLISH

 Build 5.0.2
 (GHS - Thailand)
 (ENGLISH)

Section 14. Transport information Environmental No. No. hazards **Additional** information

Special precautions for user Not available.

Transport in bulk according Not available.

to Annex II of Marpol and

the IBC Code

Section 15. Regulatory information

Regulation according to other foreign laws

Australia inventory (AICS) All components are listed or exempted. MI components are listed or exempted. **Canada inventory status**

China inventory (IECSC) Not determined.

REACH Status For the REACH status of this product please consult your company contact, as

All components are listed or exempted.

identified in Section 1.

Japan inventory (ENCS) All components are listed or exempted.

Korea inventory (KECI) Not determined. **Philippines inventory** Not determined. (PICCS)

United States inventory

(TSCA 8b)

Taiwan Chemical Substances Inventory

(TCSI)

Not determined.

Harmful Chemicals List Not listed

Section 16. Other information

History

Date of issue/Date of

revision

Date of previous issue

Prepared by

Key to abbreviations

09/02/2017.

06/08/2015. **Product Stewardship**

ACGIH = American Conference of Industrial Hygienists

CAS Number = Chemical Abstracts Service Registry Number

GHS = Global Harmonised System

IATA = International Air Transport Association, the organisation

IMDG = International Maritime Organization Rules, rules governing shipment of

goods by water.

OEL = Occupational Exposure Limit

SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average

UN Number = United Nations Number, a four digit number assigned by the United

Nations Committee of Experts on the Transport of Dangerous Goods.

Varies = may contain one or more of the following 101316-69-2, 101316-70-5, 101316-71-6, 101316-72-7, 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-64-9, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1, 74869-22-0, 90669-74-2

References Not available.

Indicates information that has changed from previously issued version.

Notice to reader

452715-TH01 **Product name** Castrol Molv Grease Product code Page: 7/8 Date of issue 09/02/2017. Language ENGLISH Version 2.01 Format GHS - Thailand (ENGLISH) Build 5.0.2 (GHS - Thailand)

Section 16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol Moly GreaseProduct code452715-TH01Page: 8/8Version 2.01Date of issue 09/02/2017.Format GHS - ThailandLanguage ENGLISHBuild 5.0.2(GHS - Thailand)(ENGLISH)