

HVG 28

Silicone Valve And Packing Grease

Benefits :

- Non toxic food grade grease.
- Offers good resistance to solvents like Methanol, Isopropanol, Acetone, Methyl Ethyl Ketone, Diethylene Glycol, Ethanol and hot and cold water.
- Does not affect plastic or rubber parts.
- Strong adhesive sealant.
- None melting.
- Stable over wide range temperature band of (-) 40°C to (+) 260°C.

Applications :

- For lubrication of valves used in chemical industry and hot and cold water lines.
- As a lubricant for plastic and rubber parts.
- For lubrication and protection of O-rings, rubber seals and other rubber assemblies.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Translucent, tacky
Colour	Visual	–	White
Base [Thickener]	–	–	Non Soap
Base Oil	–	–	Silicone
NLGI Grade	–	–	# 3
Worked Penetration	ASTM D-217	0.1 mm	220 – 250
Dropping Point	ASTM D-2265	°C	None
Oil Separation @ 100°C, 24 hrs	*CTM	%	< 1
Operating Temperature Range	–	°C	-40/+260

*CTM=Corporate Test Method

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.6 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com