

Material Safety Data Sheet

Hanval Inc Date Prepared: 03/29/2020

Date Printed: 03/29/2020

TECTYL 506

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: TECTYL 506

General or Generic ID: RUST PREVENNTIVE

Company

HANVAL INC.

13th Floor, KSCFC Bldg 395-70 Shindaebang-Dong Dongjak-Ku, Seoul, Korea

Telephone Numbers : 82-2-3284-3381~2
FAX Number : 82-2-3284-3399

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	%(by weight)
DISTILLATES (PETROLEUM) HYDROTREATED LIGHT CALCIUM SALT OF OXIDIZED PETROLATUM	64742-47-8 68425-34-3	30.0-40.0 60.0-70.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate preexisting disorders of these organs: central nervous system effects.

Developmental Information No data

Cancer Information
No data

Other Health Effects
No data

Primary Route(s) of Entry
Inhalation, Skin contact.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting.

5. FIRE FIGHTING MEASURES

Autoignition Temperature
No data

Hazardous Products

May form: carbon dioxide and carbon monoxide, sulfur compounds, various hydrocarbons.

Fire and Explosion Hazards

Vapors are heavier than air and may travel along the ground or be moved by ventilation. Flames and ignition sources are recommended to be kept distant from the material.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water may be used to extinguish fire by cooling, and diluting liquid with water. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective

equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers should be bonded when material is transferred.

Storage

Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves such as: neoprene, To prevent repeated or prolonged skin contact, wear impervious clothing and boots..

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

```
9. PHYSICAL AND CHEMICAL PROPERTIES
```

Boiling Point (for component) 315.0 F (157.2 C) @ 760 mmHg

Vapor Pressure (for component) 2.000 mmHg @ 68.00 F

Specific Vapor Density
> 1.000 @ AIR=1

Specific Gravity
.87 @ 77.00 F

Liquid Density 7.340 lbs/gal @ 77.00 F .880 kg/l @ 25.00 C

Percent Volatiles (Including Water) 45.0 - 55.0 %

Evaporation Rate
No data

Appearance TRANSLUCENT

State

LIQUID

Physical Form No data

Color

AMBER

Odor

No data

рН

Not applicable

10. STABILITY AND REACTIVITY

Hazardous Polymerization Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, sulfur compounds, various hydrocarbons.

Chemical Stability Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101 Not applicable

Container/Mode:

DRUMS/SURFACE - NO EXCEPTIONS

RQ (Reportable Quantity) - 49 CFR 172.101 Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status
TSCA (UNITED STATES) The intentional ingredients of this product are listed.

```
CERCLA RQ - 40 CFR 302.4
None
```

SARA 302 Components - 40 CFR 355 Appendix A None

Section 311/312 Hazard Class - 40 CFR 370.2
 Immediate() Delayed() Fire() Reactive() Sudden
 Release of Pressure()

SARA 313 Components - 40 CFR 372.65 None

International Regulations

Inventory Status

DSL (CANADA) The intentional ingredients of this product are listed.

ECL (SOUTH KOREA) The intentional ingredients of this product are listed.

 ${\tt EINECS}$ (EUROPE) The intentional ingredients of this product are listed.

State and Local Regulations
California Proposition 65
None

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last Page